

CORE RANGE

**FIRECHIEF®**  
making the world a safer place

# FIRECHIEF® CTX WATER+ ADDITIVE EXTINGUISHERS

MODEL:

**FWA2**  
**FWA9-L** CTX

- 35kV dielectric test
- Squeeze grip operation
- Water spray nozzle
- Corrosion resistant finish
- 5 year guarantee



  
LITHIUM-ION  
Suitable for use on lithium-ion battery fires



FWA9-L  
100-1704



FWA2  
100-1706



# FIRECHIEF® CTX WATER EXTINGUISHERS



Our CTX Water+ Additive extinguishers offer exceptional A class performance as standard. Additionally our 9L FWA9-L has the added benefit of suitability for lithium-ion battery fires, having successfully passed the LiB NTA 8133 test.

MODEL:

**FWA2**  
**FWA9-L** CTX



## Specifications

Model	FWA2	FWA9-L
Product Code	100-1706	100-1704
Description	Firechief 2L Water+ Additive Extinguisher	Firechief 9L Water+ Additive Extinguisher
Capacity (l)	2	9
Fire Rating	13A	21A
Throw Range (m)	≥3	≥4
Discharge Time (secs)	14	50
Working Pressure (bar)	10	10
Temperature Range (°C)	+5 to +60	+5 to +60
Filled Weight (kg)	3.8	13.8
Product Height (mm)	400	610
Product Diameter (mm)	110	180
Carton Height (mm)	405	615
Carton Length (mm)	120	200
Carton Width (mm)	120	190
Packaged Weight (kg)**	4.16	14.29
Product EAN	5055377966041	5055377965938

\* Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

\*\* Includes all packaging, hose / horn and bracket.

Imported into EU by: Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Road, Dublin 4, D04 C2N4, Ireland

For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, LE15 6RB, UK | UK: 0330 999 0019 | International: +44 (0)1572 772657 | [www.firechiefglobal.com/contact-us/](http://www.firechiefglobal.com/contact-us/)