

CORE RANGE

FIRECHIEF®
making the world a safer place

FIRECHIEF® CTX 2L SPRAY FOAM EXTINGUISHER

This Firechief® CTX Foam Extinguisher is an excellent solution for multi-risk usage. Ideal for use on A class fires (wood/paper) and B class (petrol & volatile liquids), the foam forms a flame smothering seal to prevent reignition.

MODEL:
CXF2 CTX

- Kitemark certified to BS EN 3
- 5 year guarantee
- 35kV dielectric test
- Squeeze grip operation
- Internal polyethylene lining
- Spray nozzle
- Corrosion resistant finish
- Complete with bracket



CXF2
100-1674

Specifications

Model	CXF2
Product Code	100-1674
Description	Firechief® CTX 2L Foam Extinguisher
Capacity (l)	2
Fire Rating	5A 55B
Discharge Time (secs)	20
Working Pressure (bar)	15
Temperature Range (°C)	+5 to +60
Product Height (mm)	370
Product Diameter (mm)	110
Filled Weight (kg)*	3.6
Carton Height (mm)	400
Carton Length (mm)	100
Carton Width (mm)	100
Packaged Weight (kg)**	4
Product EAN	5055377963934



KM 95424
BS EN 3



* Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.
** Includes all packaging, hose / horn and bracket.

For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Rd, Dublin 4, D04 C2N4, Ireland



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com