

# DataSheet

The trusted go-to brand for fire extinguishers in the UK, Commander offers a comprehensive range of fire extinguishers. Now PFAS free across the entire range, time has proven the Commander range of fire extinguishers as a dependable choice for almost any situation – with reliable performance guaranteed.



## FOAM FIRE EXTINGUISHERS

Specified for installation in settings where there is a Class B (flammable liquids) risk in enclosed spaces, the new Commander range of fluorine-free foam fire extinguishers work by creating a dense foam blanket that rapidly spreads above the fuel surface of the fire, suppressing the oxygen supply which quickly extinguishes the fire. This creates a cooling effect that prevents reignition.

Technical Specification	FX-FFF-002-FCF	FX-FFF-003-FCF	FX-FFF-006-DCF	FX-FFF-009-DCF
Capacity	2 litre	3 litre	6 litre	9 litre
Fire Rating	5A 34B	8A 55B	21A 144B	27A 183B
Extinguishing Medium	Fluorine Free Foam	Fluorine Free Foam	Fluorine Free Foam	Fluorine Free Foam
Working Pressure @ 20°C	15 bar @ 20°C	15 bar @ 20°C	15 bar @ 20°C	15 bar @ 20°C
Temperature Range	5°C to 60°C	5°C to 60°C	0°C to 60°C	0°C to 60°C
Cylinder Material	Steel	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen	Nitrogen



### PRODUCT CODE

FX-FFF-002-FCF | FX-FFF-003-FCF |  
FX-FFF-006-DCF | FX-FFF-009-DCF

### PRODUCT GROUP

Commander® Extinguishers

### DIMENSIONS (mm) (height x width x diameter)

FX-FFF-002-FCF: 284 x 144 x 117  
FX-FFF-003-FCF: 440 x 255 x 125  
FX-FFF-006-DCF: 530 x 295 x 170  
FX-FFF-009-DCF: 605 x 305 x 195

### WEIGHT

FX-FFF-002-FCF: 3.7kg  
FX-FFF-003-FCF: 5.28kg  
FX-FFF-006-DCF: 9.25kg  
FX-FFF-009-DCF: 14.5kg

- Kitemarked to BS EN3
- MER/MED approved
- UKCA and CE approved
- 35kVa Dielectric test certified
- Plastic base skirt for protection
- Polyethylene internal lining
- Full range of spare parts available
- 5-year warranty

