



Section 1

FIRE FIGHTING EQUIPMENT

FirePower

POWDER EXTINGUISHER - Stored Pressure

- Suitable for class A B C fires
- CE approved nickel plated brass valve (2kg model)
- CE approved anodized aluminium (6kg/12kg models)
- CE approved phosphated steel cylinder with polyester powder coating
- High performance dry chemical powder according to BS EN615
- 100% leak detected
- Pressure release valve included
- Production under ISO9001 quality system
- CE, UKCA, BS EN3, BSI Kitemark
- 5 year warranty

Model Number	FPP2A	FPP6	FPP12
Capacity (kg)	2	6	12
Cylinder Diameter (mm)	110	150	190
Fire Rating	13A/70B/C	43A/233B/C	55A/233B/C
BSI Kitemark	YES	YES	YES
MED Approved	NO	NO	NO
Extinguisher Weight (kg)	3.5	9.4	18
Range of Throw (m)	>2	>4	>8
Duration of Discharge (secs)	>12	>15	>27
Packing Size (LxWxH) (mm)	125x125x410	165x165x540	205x205x630
Working Pressure (bar) at 20°C	14	14	14
Test Pressure (bar)	30	30	30
Operation Temperature (°C)	-30 to +60	-30 to +60	-30 to +60

