

FireShield CO2 Extinguisher

Product Specification Sheet

FireShield



Key Features

- UKCA/CE approved
- Kitemarked to BS EN3
- MED approved (2kg model)
- MER/MED approved (5kg model)
- Corrosion-resistant finish
- Full range of spare parts available
- Supplied with frost-free swivel horn (2kg model)
- Supplied with hose & horn (5kg model)
- Lug bracket included
- Squeeze grip operation
- 5 year warranty
- 10 year actual lifespan



The FireShield CO2 extinguisher is a durable, cost-effective solution for flammable liquid and electrical fires. Safe for electronics, it's ideal for server rooms and data centers. Tested for heavy-duty marine use, it features robust alloy construction and brass fittings.



Technical Specifications

Specifications	CO001/001	CO001/002
Capacity	2kg	5kg
Fire Rating	34B	70B
Extinguishing Medium	CO2	CO2
Working Pressure	56 Bar	56 Bar
Temperature Range	-20°C - +60°C	-20°C - +60°C
Cylinder Material	Alloy Steel	Alloy Steel
Height	585mm	760mm
Width	165mm	180mm
Diameter	105mm	140mm
Weight	6.95kg	14.5kg



0330 058 0631



www.fireprotectionshop.co.uk