

FireShield ECO Water Extinguisher

Product Specification Sheet

FireShield



Key Features

- UKCA/CE approved
- Kitemarked to BS EN3
- MED and MER approved (6 & 9ltr models only)
- Environmentally friendly
- Built to last - ideal for harsh environments
- Strong base skirt
- Polyethene internal lining
- 35kVa Dielectric test certified
- 5 year warranty



The FireShield ECO Water Extinguisher is available in 3ltr, 6ltr, and 9ltr sizes with strong fire ratings (13A-27 A). Ideal for Class A fires (wood, paper, etc.). The Water ECO extinguisher is perfect for hospitals, hotels, supermarkets, and more.

Technical Specifications

Specifications	WAE001/001	WAE001/002	WAE001/003
Capacity	3ltr	6ltr	9ltr
Fire Rating	13A	21A	27A
Extinguishing Medium	Water + Additive	Water	Water
Working Pressure	12 Bar	12 Bar	12 Bar
Temperature Range	+5°C -+60°C	+5°C -+60°C	+5°C -+60°C
Cylinder Material	Steel	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen	Nitrogen
Height	435mm	501mm	576mm
Width	240mm	185mm	198mm
Diameter	140mm	160mm	185mm
Weight	5.44kg	9.3kg	14kg



0330 058 0631



www.fireprotectionshop.co.uk