

# FireShield LFX Lithium-Ion Fire Extinguishers



Product Code: FPS/LITH001

Agent	LFX
Capacity	3
Fire Performance	13A
Working pressure (bar) at 20°C	15
Max. Service Pressure (bar)	20
Temperature range	+5 - +60
Discharge time (secs) at 20°C	25 - 30
Cylinder	Lined Steel
Certification	BS EN3, MED, MSR, PED, UKCA, CE
Dimensions (H x W x D) in mm	435 x 188 x 441
Weight (Kg)	5.8



Product Code: FPS/LITH002


Agent	LFX
Capacity	6
Fire Performance	27A
Working pressure (bar) at 20°C	15
Max. Service Pressure (bar)	20
Temperature range	+5 - +60
Discharge time (secs) at 20°C	47 - 53
Cylinder	Lined Steel
Certification	NTA 8133, BS EN3, MED, MSR, PED, UKCA, CE
Dimensions (H x W x D) in mm	568 x 206 x 510
Weight (Kg)	10



Product Code: FPS/LITH003

Agent	LFX
Capacity	9
Fire Performance	34A
Working pressure (bar) at 20°C	15
Max. Service Pressure (bar)	20
Temperature range	+5 - +60
Discharge time (secs) at 20°C	72 - 78
Cylinder	Lined Steel
Certification	NTA 8133, BS EN3, MED, MSR, PED, UKCA, CE
Dimensions (H x W x D) in mm	662 x 228 x 572
Weight (Kg)	14.3

**Lithium-ion  
Range:**





# FireShield

## FireShield LFX Range

We have a full range of products to ensure you can effectively manage the Lithium-Ion Battery fire risk within your specific environment



### Stands & ID Signs

Ensure that your FireShield LFX Fire Extinguisher are clearly identifiable with the correct Lithium-Ion Battery ID signs and Stands.



### Bundles

Purchase your LFX Fire Extinguishers and our robust, all-weather containers together for added value - available in in single or double, and for 6ltr & 9ltr units.



### Blankets

Protect against large lithium-ion battery fires with a combination of LFX Fire Extinguishers and a large Lithium-Ion fire blanket.



6m x 8m single-use or multi-use Fire Blanket



FireShield Heavy Duty Fire Blanket



3m x 3m Premium single-use or multi-use Fire Blanket