

DataSheet

The trusted go-to brand for fire extinguishers in the UK, Commander offers a comprehensive range of fire extinguishers. Now PFAS free across the entire range, time has proven the Commander range of fire extinguishers as a dependable choice for almost any situation – with reliable performance guaranteed.



FOAM FIRE EXTINGUISHERS

Specified for installation in settings where there is a Class B (flammable liquids) risk in enclosed spaces, the new Commander range of fluorine-free foam fire extinguishers work by creating a dense foam blanket that rapidly spreads above the fuel surface of the fire, suppressing the oxygen supply which quickly extinguishes the fire. This creates a cooling effect that prevents reignition.

| Technical Specification | FX-FFF-002-FCF | FX-FFF-003-FCF | FX-FFF-006-DCF | FX-FFF-009-DCF |
|-------------------------|--------------------|--------------------|--------------------|--------------------|
| Capacity | 2 litre | 3 litre | 6 litre | 9 litre |
| Fire Rating | 5A 34B | 8A 55B | 21A 144B | 27A 183B |
| Extinguishing Medium | Fluorine Free Foam | Fluorine Free Foam | Fluorine Free Foam | Fluorine Free Foam |
| Working Pressure @ 20°C | 15 bar @ 20°C | 15 bar @ 20°C | 15 bar @ 20°C | 15 bar @ 20°C |
| Temperature Range | 5°C to 60°C | 5°C to 60°C | 0°C to 60°C | 0°C to 60°C |
| Cylinder Material | Steel | Steel | Steel | Steel |
| Pressuring Gas | Nitrogen | Nitrogen | Nitrogen | Nitrogen |



PRODUCT CODE

FX-FFF-002-FCF | FX-FFF-003-FCF |
FX-FFF-006-DCF | FX-FFF-009-DCF

PRODUCT GROUP

Commander® Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FX-FFF-002-FCF: 284 x 144 x 117
FX-FFF-003-FCF: 440 x 255 x 125
FX-FFF-006-DCF: 530 x 295 x 170
FX-FFF-009-DCF: 605 x 305 x 195

WEIGHT

FX-FFF-002-FCF: 3.7kg
FX-FFF-003-FCF: 5.28kg
FX-FFF-006-DCF: 9.25kg
FX-FFF-009-DCF: 14.5kg

- Kitemarked to BS EN3
- MER/MED approved
- UKCA and CE approved
- 35kVa Dielectric test certified
- Plastic base skirt for protection
- Polyethylene internal lining
- Full range of spare parts available
- 5-year warranty

