

# FIRECHIEF® WHEELED CARBON DIOXIDE EXTINGUISHERS

**FIRECHIEF®**  
making the world a safer place

MODEL:

**FXC10-B**

**FXC30-B**

- Clean and highly effective
- Safe on electrical equipment
- One person operation
- One person movement
- Conforms to EN1866-1
- Certified to the Pressure Equipment Directive PED 2014/68/EU, and to the Marine Equipment Directive 2014/90/EU.



FXC30-B  
100-1676

FXC10-B  
100-1675



+44 (0) 330 999 0019

[sales@firechiefglobal.com](mailto:sales@firechiefglobal.com)

[firechiefglobal.com](http://firechiefglobal.com)

# FIRECHIEF® WHEELED CARBON DIOXIDE EXTINGUISHERS

**FIRECHIEF®**  
making the world a safer place

This fire extinguisher has been designed to be used in the industrial sector and is also suitable for use in marine and maritime field. It can be used on live electrical equipment. The wheeled fire extinguisher is intended for use in high fire risk areas, which requires high extinguisher performance levels.

All units conform to EN1866-1, and are certified to the Pressure Equipment Directive PED 2014/68/EU, and the Marine Equipment Directive 2014/90/EU.

## CO2 CARBON DIOXIDE

Carbon dioxide is an inert gas which is charged in a cylinder in liquid form. It is an extinguishing agent and it does not require additives or other substances to perform its function. The extinguishing action takes place from the replacement of the oxygen necessary for combustion with inert gas. The power of the jet both removes the fuel (oxygen) and lowers the flames. During the dispensing the temperature difference between the dispensed liquid (-78 °C) and the surrounding environment allows the creation of condensation (CO2 snow) quickly reducing the temperature of the fire. The delivery is through a cone with diffuser. Carbon dioxide can be used on B class fires (flammable liquids, oils and paints, etc ...) and is suitable for use on live equipment.

**MODEL:**

**FXC10-B**

**FXC30-B**



## Specifications

Model	FXC10-B	FXC30-B
Product code	100-1675	100-1676
Capacity (kg)	10	30
Fire rating	113 B	144 B
Discharge time (secs)	15	27
Working pressure (bar)	174	200
Test pressure (bar)	250	300
Temperature range (°C)	-30/+60	-30/+60
Hose length (m)	Hose - 6 / Hose & horn - 6.8	Hose - 6 / Hose & horn - 6.8
Product height (mm)	980	1280
Product diameter (mm)	156	229
Filled weight (kg)	42	104

Imported into EU by: Firechief® Global (EU) Ltd, 3rd Floor, 40 Mespil Road, Dublin 4, D04 C2N4, Ireland

For more information contact: Firechief® Global, 3 Lands End Way, Oakham, Rutland, LE15 6RB, UK | UK: 0330 999 0019 | International: +44 (0)1572 772657 | [www.firechiefglobal.com/contact-us/](http://www.firechiefglobal.com/contact-us/)

 +44 (0) 330 999 0019

 [sales@firechiefglobal.com](mailto:sales@firechiefglobal.com)

 [firechiefglobal.com](http://firechiefglobal.com)