



JUNO 65

IP65 EMERGENCY NM TWIN SPOT

JUNO 65 is the ideal solution for adjustable, non-maintained emergency lighting in any wet or dusty environment. The high light output suits higher mounting applications where flexibility is a prime consideration

Features

- LiFePO4 Batteries
- Selectable Self / Manual Test Emergency
- IP65
- Fully adjustable LED projector flood heads
- IK08

Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
JUN65/500/ST/V2	Juno 65 NM EM Twin Spot Selectable ST/M 3 Hr 500lm IP65	500lm	500 lm	4.5W	111 lm/W

Product Information

Warranty	5 Years
Emergency Battery Warranty	5 Years
On-Site Warranty	2 Years
Colour Appearance (CCT)	6500K
IP Rating	IP65
IK Rating	IK08
Emergency Battery Type	LiFePO4
Voltage	220-240V
Material (Body/Housing)	Polycarbonate
Material (Diffuser/Cover)	Polycarbonate

Colour Rendition (CRI)	Ra >80
Colour Finish	White RAL9003
LED Life Expectancy	36000 Hours
Power Factor	>0.3
Frequency	50/60Hz
Driver Type	Fixed
Approval	UKCA CE
Electrical Class	Class II
Working Temperature	0°C to +45°C
EM Working Temperature	0°C to 45°C



JUNO 65

IP65 EMERGENCY NM TWIN SPOT

Packaging Information

Dimensions (mm)	L: 300 x W: 288 x D: 69 mm
Product Net Weight (kg)	1.139 kg
Barcode	5055807628440
Box Dimensions (mm)	L: 314 x W: 292 x D: 73 mm
Box Gross Weight (kg)	1.32 kg

Units/Outer Carton	10
Outer Carton Barcode	15055807628447
Outer Carton Dimensions (mm)	L: 605 x W: 330 x D: 390 mm
Outer Carton Gross Weight (kg)	14.2 kg