

WET CHEMICAL FIRE EXTINGUISHERS

- Wet Chemical fire extinguishers: contain no fluorine, silicone or PFAS, PFOA or PFOS
- Stored pressure 2ltr, 3ltr & 6ltr available
- Supplied with bracket
- Kitemarked to BS EN 3
- CE approved
- 5-year warranty



	TITANCOREFFWC2	TITANCOREFFWC3	TITANCOREFFWC6
Capacity	2 litres	3 litres	6 litres
Fire rating	5A 40F	8A 75F	13A 75F
Extinguishing medium	Fluorine-free Wet Chemical FireFilm-KF	Fluorine-free Wet Chemical FireFilm-KF	Fluorine-free Wet Chemical FireFilm-KF
Cylinder height	317mm	353mm	452mm
Cylinder diameter	110mm	130mm	162mm
Filled weight	4.20kg	6.20kg	11.20kg
Working pressure	12 bar	12 bar	12 bar
Test pressure	27 bar	27 bar	27 bar
Temperature range	+5°C-+60°C	+5°C-+60°C	+5°C-+60°C
Pressuring gas	Nitrogen	Nitrogen	Nitrogen
Cylinder material	ST12	ST12	ST12
Volume	2.40 litres	3.90 litres	7.50 litres
Pallet quantity	300	98	60
BS EN 3 Kitemark	✓	✓	✓
CE	✓	✓	✓